

## Cisco Unified IP Phone 7942G

### Product Overview

Cisco® Unified Communications Solutions unify voice, video, data, and mobile applications on fixed and mobile networks, delivering a media-rich collaboration experience across business, government agency, and institutional workspaces. These applications use the network as the platform to enhance comparative advantage by accelerating decision time and reducing transaction time. The security, resilience, and scalability of the network enable users in any workspace to easily connect anywhere, anytime, and anyplace, using any media, device or operating system. Cisco Unified Communications is part of a comprehensive solution that includes network infrastructure, security, wireless, management applications, lifecycle services, flexible deployment and outsourced management options, and third-party applications.

The Cisco Unified IP Phone 7942G (Figure 1) is a full-featured IP phone with speakerphone and handset designed for wideband audio. It is intended to meet the needs of needs of transaction-type workers with significant phone traffic. It has two programmable backlit line/feature buttons and four interactive soft keys that guide you through all call features and functions. The phone has a large, 4-bit grayscale graphical LCD (Figure 2) that provides features such as date and time, calling party name, calling party number, digits dialed, and presence information. The crisp graphic capability of the display allows for the inclusion of higher value, more visibly rich Extensible Markup Language (XML) applications, and support for localization requiring double-byte Unicode encoding for fonts. A hands-free speakerphone and handset designed for hi-fidelity wideband audio are standard on the Cisco Unified IP Phone 7942G, as is a built-in headset connection and an integrated Ethernet switch.

**Figure 1.** Cisco Unified IP Phone 7942G



**Figure 2.** Close-Up of Display and Lighted Line Keys



**Features and Benefits**

The Cisco Unified IP Phone 7942G is designed to grow with your organization and enhancements to your system capabilities. The dynamic feature set allows the phone to keep pace with your requirements through regular software updates. Firmware changes can be downloaded from Cisco.com. No hands-on moves and changes are required with the phone—you can simply pick up the phone and move to a new location anywhere on your network. The Cisco Unified IP Phone 7942G also provides many accessibility features. Table 1 lists the phone's features.

**Table 1.** Cisco Unified IP Phone 7942G Features

| Feature  | Description/Benefit   |
|--|---|
| <b>Display</b>                                 | 5-inch (12.5 cm), high-resolution (320 x 222), graphical monochrome 4-bit grayscale display. Allows for greater flexibility of features and applications, and significantly expands the information viewed when using features such as Services, Information, Messages, and Directory. Display also supports localization requiring double-byte Unicode encoding for fonts.   |
| <b>Wideband Audio</b>                          | Support for wideband (G.722 codec, adherence to TIA 920), including handset, headset, and speakerphone (see Q&A for details).   |
| <b>Codec Support</b>                           | G.711a, G.711μ, G.729a, G.729ab, G.722, and iLBC audio compression codecs are supported (see Q&A for details).  |
| <b>Speakerphone</b>                            | Full-duplex speakerphone with acoustic echo cancellation.   |
| <b>Messages Key</b>                            | Provides direct access to voicemail.  |
| <b>Directories Key</b>                         | Ready access to missed, received, and placed calls (plus intercom history and directories). Incoming messages are identified and categorized on the display, allowing users to quickly and effectively return calls using direct dial-back capability. Corporate directory integrates with the Lightweight Directory Access Protocol Version 3 (LDAP3) standard directory.  |
| <b>Settings Key</b>                            | Allows user to adjust display contrast, select background images (if available), and select ringer sounds through the User Preference menu. Network Configuration preferences also can be set up (usually by the system administrator). Configuration can be set up either automatically or manually for Dynamic Host Control Protocol (DHCP), Trivial File Transfer Protocol (TFTP), Cisco Unified Communications Manager, and backup Cisco Unified Communications Manager instances. Other available Settings submenus include Device Configuration, Security Configuration, and Model Information. |
| <b>Services Key</b>                            | Allows users to quickly access diverse information such as weather, stocks, quote of the day, or any Web-based information using XML.   |
| <b>Help Button</b>                             | Online Help gives users information about the phone keys, buttons, and features.  |
| <b>Speakerphone, Mute, and Headset Buttons</b> | Speakerphone includes Speaker On/Off, Microphone Mute, and Headset buttons that are lit when active. For added security, the audible dual tone multifrequency (DTMF) tones are masked when the speakerphone mode is used.   |

| Feature   | Description/Benefit   |
|---|---|
| <b>Ethernet Switch</b>                                | Internal 2-port Cisco Ethernet switch allows for a direct connection to a 10/100BASE-T Ethernet network through an RJ-45 interface with single LAN connectivity for both the phone and a colocated PC. System administrator can designate separate VLANs (802.1Q) for the PC and phone, providing improved security and reliability of voice and data traffic.    |
| <b>Headset Port</b>                                   | Dedicated headset port eliminates the need for a separate headset amplifier and allows the handset to remain in its cradle, making headset use simpler. Both wideband (G.722) and narrowband headsets are supported.  |
| <b>Volume Control</b>                                 | Provides easy decibel-level adjustments for the speakerphone, handset, headset, and ringer. The handset is hearing aid-compatible. Additional volume control gain can be achieved using an inline headset amplifier.  |
| <b>Adjustable Foot-Stand</b>                          | Stand is adjustable from flat to 60 degrees to provide optimum display viewing and comfortable use of all buttons and keys. The foot-stand is keyed to match standard wall-jack configurations for wall mounting. Optional wall-mount brackets are also offered.  |
| <b>Multiple Ring Tones</b>                            | More than 24 defined user-selectable ring tones are available. Ring tones may also be personalized through use of the Cisco Unified Phone Application Suite.  |
| <b>Americans with Disabilities Act (ADA) Features</b> | Handset is hearing aid-compatible and meets Federal Communications Commission (FCC) loudness requirements for the Americans with Disabilities Act (ADA). Section 508 loudness requirements can be achieved using industry-standard inline headset amplifiers such as Walker Equipment W-10 or CE-100 amplifiers. Dial pad is also ADA-compliant.                  |
| <b>Quality of Service (QoS) Options</b>               | Supports differentiated services code point (DSCP) and 802.1Q/p standards.  |
| <b>Security</b>                                       | Positive device identity through X.509v3 Certificates, digitally signed images, cryptographically secure provisioning, and secure signaling and secure media with AES-128. Cryptography is not enabled by default and may only be enabled through a cryptographically enabled CUCM. The phone also contains an 802.1X supplicant and supports EAPOL pass-through. |
| <b>Language Support</b>                               | Built-in support for more than 30 languages (dependent on Cisco Unified Communications Manager version).  |
| <b>Configuration Options</b>                          | IP address assignment can be statically configured or configured through the DHCP client.   |

**Table 2.** Cisco Unified IP Phone 7942G Product Specifications

| Specification                      | Description  |
|------------------------------------|--|
| <b>Dimensions (H x W x D)</b>      | 8.2 x 10.5 x 6 in. (20.32 x 26.67 x 15.24 cm)  |
| <b>Weight</b>                      | 3.5 lb (1.6 kg)  |
| <b>Phone-Casing Composition</b>    | Acrylonitrile butadiene styrene (ABS) plastic in textured dark gray color with silver bezel  |
| <b>Power</b>                       | Supports IEEE 802.3af PoE (Class 2). Also supports Cisco Prestandard Power over Ethernet (PoE), allowing powering from any of the Cisco Inline Power-capable blades and boxes, plus Cisco midspan. 48VDC is required; it can be supplied locally at the desktop using an optional AC-to-DC power supply (part number CP-PWR-CUBE-3=) or power injector (CP-PWR-INJ=). Local power options require a corresponding AC country cord (see Table 6). |
| <b>Phone Software Requirements</b> | Supported in 8.3(2) and greater  |
| <b>Call Control Compatibility</b>  | Supported in Cisco Unified Communications Manager Versions 4.1(3)sr5b, 4.2(3)sr2b, 4.3(1), 5.1.1(b), 5.1(2), 6.0(1) and greater<br>Supported in Cisco Unified Communications Express and SRST Version 4.1  |
| <b>Signaling Protocols</b>         | Skinny Client Control Protocol (SCCP) and Session Initiation Protocol (SIP) with Cisco call control  |

**Table 3.** Temperature Ratings

| Temperature Variable         | Description               |
|------------------------------|---------------------------|
| <b>Operating Temperature</b> | 32 to 104°F (0 to 40°C)   |
| <b>Relative Humidity</b>     | 10 to 95% (noncondensing) |
| <b>Storage Temperature</b>   | 14 to 140°F (-10 to 60°C) |

## Certifications—Compliance and Safety

Refer to the following link:

[http://www.cisco.com/univercd/cc/td/doc/product/voice/c\\_ipphon/english/ipp7960/iphrcsi3.html](http://www.cisco.com/univercd/cc/td/doc/product/voice/c_ipphon/english/ipp7960/iphrcsi3.html).

## Ordering Information

To place an order, visit the [Cisco Ordering Home Page](#). To download software, visit the [Cisco Software Center](#).

**Table 4.** Ordering Information—Phone/license

| Part Number   | Description  |
|---------------|--|
| CP-7942G      | Cisco Unified IP Phone 7942G   |
| CP-7942G=     | Cisco Unified IP Phone 7942G, spare  |
| CP-7942G-CH1  | Cisco Unified IP Phone 7942G, for Channels, with one station user license  |
| CP-7942G-CCME | Cisco Unified IP Phone 7942G, for Channels, with one Cisco Unified Communications Manager Express station user license |

**Note:** All Cisco Unified IP phones require the purchase of a phone technology license, regardless of call protocol being used.

**Table 5.** Ordering Information—Accessories

| Part Number        | Description   |
|--------------------|---|
| CP-LCKNGWALLMOUNT= | Locking wall-mounting kit, flat (recommended version)   |
| CP-WALLMOUNTKIT=   | Nonlocking wall-mounting kit, slanted   |
| CP-LCKNGWALLMNT2=  | Locking wall-mounting kit, slanted  |
| CP-PWR-CUBE-3=     | Local power adapter for sites where PoE is not available; refer to Table 6 to select the correct regional power cord. CP-PWR-CUBE-3= is compatible with and can replace CP-PWR-CUBE-2=.   |
| CP-PWR-INJ=        | Single-port midspan power injector with integrated power supply, specifically designed and tested for use with all Cisco Unified IP Phones. May be used as an alternative to the existing Cisco phone local power adapter (CP-PWR-CUBE-3=) and can support a maximum distance of 100 meters between an unpowered switch and a Cisco Unified IP Phone. |

**Table 6.** Ordering Information—AC Country Power Cords

| Part Number     | Description        |
|-----------------|--------------------|
| CP-PWR-CORD-AP= | Asia Pacific       |
| CP-PWR-CORD-AR= | Argentina          |
| CP-PWR-CORD-AU= | Australia          |
| CP-PWR-CORD-CE= | European Community |
| CP-PWR-CORD-CN= | China              |
| CP-PWR-CORD-JP= | Japan              |
| CP-PWR-CORD-NA= | North America      |
| CP-PWR-CORD-SW= | Switzerland        |
| CP-PWR-CORD-UK= | United Kingdom     |

## Cisco Unified Communications Services

Cisco and our certified partners can help you deploy a secure, resilient Cisco Unified Communications solution, meeting aggressive deployment schedules and accelerating business advantage. Our portfolio of services is based on proven methodologies for unifying voice, video, data, and mobile applications on fixed and mobile networks.

Our unique lifecycle approach to services defines the requisite activities at each phase of the solution lifecycle. Customized planning and design services focus on creating a solution that meets your business needs. Award-winning technical support increases operational efficiency. Remote management services simplify day-to-day operations, and optimization services enhance solution performance as your business needs change.

## For More Information

For more information about the Cisco Unified IP Phone 7942G, visit <http://www.cisco.com/en/US/products/hw/phones/ps379/index.html> or contact your local account representative.



---

**Americas Headquarters**  
Cisco Systems, Inc.  
San Jose, CA

**Asia Pacific Headquarters**  
Cisco Systems (USA) Pte. Ltd.  
Singapore

**Europe Headquarters**  
Cisco Systems International BV Amsterdam,  
The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at [www.cisco.com/go/offices](http://www.cisco.com/go/offices).

Cisco and the Cisco Logo are trademarks of Cisco Systems, Inc. and/or its affiliates in the U.S. and other countries. A listing of Cisco's trademarks can be found at [www.cisco.com/go/trademarks](http://www.cisco.com/go/trademarks). Third party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1005R)